

## AD-XVR5116N



### Key Features

- Support H.265/H.264 video formats
- Support audio over coaxial cable
- Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
- 16-channel BNC input
- Support 1-ch HDMI output, 1-ch VGA output at up to 1920\*1080
- Long transmission distance over NT-XVR5116Nx cable

### Specifications

| Model                         | NT-XVR5116N   |
|-------------------------------|---|
| Video/Audio Input             |   |
| Analog Video Input            | 16-ch, BNC  |
| IP Video Input                | 8-ch(only IP up to 24ch), each channel up to 8MP  |
| Supported Analog Camera Types | <p>Support AHD input:<br/>5MP@12fps - 4MP@15fps - 1080P@30fps - 720P@30fps</p> <p>Support TVI input:<br/>5MP@12fps - 4MP@15fps - 1080P@30fps - 720P@30fps</p> <p>Support CVI input:<br/>4MP@15fps - 1080P@30fps - 720P@30fps - Support CVBS input</p> |

|                           |  |  |
|---------------------------|--|--|
| Audio Input               | 1-ch, RCA  |  |
| Two-way Audio             | 1-ch, RCA  |  |
| <b>Network</b>            |  |  |
| Incoming Bandwidth        | 40Mbps   |  |
| Outgoing Bandwidth        | 64Mbps   |  |
| Remote Users              | 128  |  |
| Protocols                 | TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE  |  |
| <b>Video/Audio Output</b> |  |  |
| VGA Output                | 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz   |  |
| HDMI Output               | 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz   |  |
| Audio Output              | 1-ch, RCA  |  |
| Synchronous Playback      | 16-ch  |  |
| <b>Encoding</b>           |  |  |
| Recording Resolution      | 5MP Lite/4MP Lite/1080P/720P/4CIF/CIF  | 5MP Lite/4MP Lite /1080P/720P/4CIF/CIF |
| Recording Frame Rate      | <b>Main stream:</b><br>5MP Lite@6fps<br>4MP Lite@8fps<br>2MP Lite@15fps<br>2MP@8fps<br>720P@15fps<br><b>Sub stream:</b><br>D1@15fps(Max) |  |
| <b>Hard Disk</b>          |  |  |
| SATA                      | 1 SATA interface   |  |
| Capacity                  | Up to 6TB for each HDD   |  |
| <b>External Interface</b> |  |  |
| Network Interface         | 1RJ45 10M/100M self-adaptive Ethernet Interface  |  |
| USB Interface             | Rear panel:2 x USB2.0  |  |
| <b>General</b>            |  |  |
| Power Supply              | 12V DC<br>Power Consumption: ≤ 8 W( without HDD )  |  |
| Working Environment       | -10°C ~ + 55°C ( +14°F ~ +131°F ), Humidity ≤ 90% RH(non-condensing)   |  |
| Dimensions(W×D×H)         |  |  |
| Weight ( without HDD )    | ≤1.1 Kg ( 2.42lb )   |  |