


AI Face Recognition Access Control Time Attendance **AD-705F**

 C#/Java
 SDK provided

 Cloud
 Software

ADVISION



-  **5000**
FACE CAPACITY
-  **10000**
FINGERPRINT CAPACITY
-  0.5~2.5 Meters
Recognition Distance
-  **LIVE FACE DETECTION**
-  **5 INCH TOUCH SCREEN**
-  **QR CODE READING**
-  **ACCESS CONTROL**
-  **RFID SUPPORT**
-  **PHOTO CAPTURE**
-  **MASK DETECTION**

Specifications

Model	AD-705F
Hardware	
CPU	1.2G Dual-Core ARM Cortex-A7
NPU	600G (0.6T)
RAM	256M DDR3L
ROM	4G EMMC
Camera	Real Sensor 1/2.9 inch FOV 75° 2MP pixel high-definition color camera WDR wide dynamic Sensor 1/5 inch FOV 75° 2MP pixel infrared live camera
Fill Light	LED Fill Light and Dual Infrared Fill Light (Automatic control according to ambient light)
Display	5.0 Inch IPS Touch Screen, HD 720*1280
Communication port	TCP/IP, USB-Type A(Support U disk), Wifi, RS485
Product Size	188mm*80mm*20mm
Power	DC 12V, 2A
Working Temperature	0~45 °C
Working Environment	Under normal light, strong light, dark environment, backlight
Material	Aluminum alloy case
Firmware Specs	
OS	Linux 3.0
Language	English, Spanish, Arabic, Thai, Russian, Portuguese, French, Farsi, Vietnamese, Japanese, Turkish, and customizable
Verify Method	Face Recognition, Fingerprint, ID Card(IC optional), Password or combination
QR Code Scanner	Support(Scan by camera)
Face/Card/Password	5,000(50,000 optional)
Capacity	
Fingerprint Capacity	10,000(100,000 optional)
Logs Capacity	500,000
Face Recognition Speed	<0.2S
Face Recognition Distance	0.5~2.5 meters(adjustable)
Live Face Detection	Reject Photo and Video
Mask Detection	Support mask detection and face recognition with wearing mask
Access Control Interface	
Relay output	One set
Alarm output	One set
Fire Input	One set
Door sensor	Support
Wiegand	One set WG 26/34 Input/Output
Exit button	Support
Door Bell	Support
Tamper Alarm	Support
Anti-pass back	Support
Interlock	Support

Multi-Mode Access Identification



Face Recognition



RFID Card



QR Code Reading



Fingerprint

